



FLEXIBLE CABLE Cu SYLCONIC RUBBER INSULANT +180°C (FG4/2)

BL	1,5 mmq	BLUE	Gre	1 mmq	GREEN
WH	1,5 mmq	WHITE	re	0,5 mmq	RED
BR	1,5 mmq	BROWN	bl	0,5 mmq	BLUE
BK	1,5 mmq	BLACK	wh	0,5 mmq	WHITE
GV	1 mmq	YE-GREE	br	0,5 mmq	BROWN
Re	1 mmq	RED	bk	0,5 mmq	BLACK
Vi	1 mmq	VIOLET	gr	0,5 mmq	GREY
Ye	1 mmq	YELLOW	Other	(non 0370035)	

- LENGTHS EXPRESSED IN Cm TO CUT, BEFORE CRIMPING (tolerances +/- 1cm)
- CONVERGENTING WIRES ARE CRIMPED IN THE SAME FASTON
- COMMUTATOR FASTON: FLAG SLOW INSERTION CS COLOMBO or INARCA
- “A”: FEMAL FASONT STRIGHT 6.3mm x 0.8 Ir.Ni
- “BA-A”: ROLLED FLAG FASTON 6.3mm x 0.8 Ir.Ni
- “CF”: FRONTAL INSERTION FASTON COVER T105
- “PGB”: FASTON PG-BACK 6.3mm x 0.8 CuZnTin
- “4.8”: FASTON 4.8mm x 0.8 Cu-Zn Tin
- OTHERS : FEMALE STRAIGHT FASTONS 6.3mm x 0.8 CuZnTin